

Aluminum Expanded Metal

Style Designation	Strand Width	Wt. in Lbs. per Sq. Ft.	Inventoried Sheet Sizes	Approx. Size of Mesh Center to Center of Bridges		Strand Thickness (in inches)	Standard Gauge Used	No. Dia. in 12 inch of Width	Opening size	Open area
				Width	Length					
" No. 20	.086 in	.82 1.24	4' x 8'	.25 in	1.018 in	.029 in	20	48	.094 x .688	30 - 35 %
" No. 18	.080 in	1.08 1.65	4' x 8'	.25 in	1.024 in	.042 in	18	48	.094 x .688	35 - 40 %
" No.18	.106 in	.69	4' x 8'	.500 in	1.26 in	.039 in	18	24	.320 x 1.03	55 - 60 %
" No.16	.106 in	.86	4' x 8'	.500 in	1.26 in	.051 in	16	24	.300 x .950	57 - 62 %
" No.18	.127 in	.46	4' x 8'	.923 in	2.100 in	.039 in	18	13	.673 x 1.783	71 - 75 %
" No.16	.121 in	.57	4' x 8'	.923 in	2.100 in	.051 in	16	13	.683 x 1.763	71 - 76 %
" No.13	.125 in	.88	4' x 8'	.923 in	2.100 in	.079 in	13	13	.636 x 1.710	71 - 76 %
" No. 9	.170 in	1.98	4' x 8'	.923 in	2.100 in	.127 in	10	13	.630 x 1.562	60 - 65 %
½" No.16	.132 in	.43	4' x 8'	1.33in	3.150 in	.051 in	16	9	1.072 x 2.725	78 - 83 %
½" No.13	.135 in	.66	4' x 8'	1.33 in	3.150 in	.079 in	13	9	1.048 x 2.660	78 - 83 %
½" No. 9	.171 in	1.33	4' x 8'	1.33 in	3.150 in	.125 in	10	9	1.015 x 2.545	72 - 77 %

Heanjia Super-Metals Co., Ltd

www.nickel-wiremesh.com