

Inconel Perforated Metal Specification

Hole diameter, mm	Distance from center of hole,	Side distance	No. of holes dm2	Empty area
0.85 mm	1.6 mm	2.8	4500	25.6 %
0.85 mm	1.7 mm	3	3985	22.5 %
0.85 mm	1.8 mm	3.2	3560	20 %
0.85 mm	2 mm	3.5	2880	16.2 %
0.9 mm	1.8 mm	3.2	3560	22.5 %
0.9 mm	2 mm	3.5	2880	18.2 %
1 mm	2 mm	3.5	2880	22.7 %
1 mm	2.25 mm	3.9	2880	17.8 %
1 mm	2.3 mm	4	1840	14.5 %
1 mm	2.5 mm	4.3	1840	14.5 %
1 mm	3	5.2	1280	10 %
1 mm	4 mm	7	720	5.6 %
1 mm	5 mm	8.7	460	3.6 %
1.25 mm	2.25 mm	3.9	2280	28 %
1.25 mm	2.5 mm	4.3	1840	22.7 %
1.25 mm	3 mm	5.2	1280	15.6 %
1.4 mm	3 mm	5.2	1280	19.5 %
1.4 mm	3.5 mm	6	940	14.4 %
1.5 mm	2.5 mm	4.3	1840	32.7 %
1.5 mm	2.75 mm	4.8	1530	26.7 %
1.5 mm	3 mm	5.2	1280	22.7 %
1.5 mm	3.5 mm	6	940	16.5 %
1.5 mm	4 mm	7	720	12.8 %
2 mm	3 mm	5.2	1280	31 %
2 mm	3.25 mm	5.3	1089	34 %
2 mm	3.6 mm	6.3	890	28 %
2 mm	3.75 mm	6.5	820	25.75 %
2 mm	4 mm	7	720	22.7 %
2 mm	4.5 mm	7.8	570	17.7 %
2 mm	5 mm	8.7	460	14.4 %
2 mm	6 mm	10.4	320	10 %
2 mm	8 mm	13.8	180	5.7 %
2 mm	10 mm	17.3	115	3.6 %
2 mm	12 mm	20.7	80	2.5 %
2.5 mm	3.5 mm	6	940	38 %
2.5 mm	4 mm	7	720	28.8 %