

Nichrome Expanded Metal Sheet Specification

Strand Width	Wt. in Lbs. per Sq. Ft. Galv.	Sheet Sizes	Approx. Size of Mesh Center to Center of Bridges		Strand Thickness	Standard Gauge Used	Approx. No. Dia. in 12 inch of Width	Approx. Size of Opening	Open Area
			Width	Length					
.108 in	.25	4' x 8'	.500 in	1.26 in	.045 in	16	24	.300 x 1.03 (inches)	58 to 63 %
.109 in	.41	4' x 8'	.500 in	1.26 in	.067 in	12	24	.250 x .920 (inches)	55 to 60 %
.132 in	.16	4' x 8'	.923 in	2.125 in	.040 in	16	13	.750 x 1.781 (inches)	70 to 75 %
.141 in	.30	4' x 8'	.923 in	2.125 in	.070 in	12	13	.750 x 1.781 (inches)	67 to 72 %
.182 in	.38	4' x 8'	.923 in	2.125 in	.070 in	12	13	.688 x 1.781 (inches)	60 to 65 %
.212 in	.61	4' x 8'	.923 in	2.125 in	.095 in	8	13	.600 x 1.750 (inches)	53 to 58 %
.138 in	.20	4' x 8'	1.33 in	3.125 in	.070 in	12	9	1.062 x 2.750 (inches)	73 to 78 %
.240 in	.40	4' x 8'	1.33 in	3.125 in	.095 in	8	9	1.000 x 2.750 (inches)	63 to 68 %

Contact us for small to large hole sizes in standard and custom patterns.

Heanjia Super-Metals Co., Ltd

www.nickel-wiremesh.com